



NEMA Frame

Foot Mounted

3PH, 60 Hz

Aluminum Construction

0.5 - 15 HP

Performance - Page 51
Dimensions - Pages 33 - 34



EPACT
C.C. 047A

Features:

- Meets EPAct Efficiency requirements
- Totally Enclosed Fan Cooled Enclosure
- IP55 degree of protection
- NEMA Design B
- Class F insulation
- Electrical Connection: 0.5 - 15HP connected Star (575v),
0.5 - 15HP (230/460 & 208/416v) 9 leads Series Parallel Star.
- Service Factor 1.15
- C & D Flanges available
- Flexible Conduit Box Location
(Available as Top, Right or Left Mounted)
- Easy conversion to F1, F2 (Fitted removable mounting feet)
- Double drilled feet
- Double Shielded Ball Bearings
- Drainage holes in lowest points of the motor
- UL Listed, CSA Certified, CE marked
- **CSA approved for Class I ; Division II ; Groups A,B,C & D**
- Warranty: 2 years

HP	RPM	FRAME	208/416V	230/460V	575V	LIST
0.5	900	143T	WA8N.50-3	WA8N.50-4	WA8N.50-5	\$528
	1200	145T	WA6N.75-3	WA6N.75-4	WA6N.75-5	413
0.75	900	145T	WA8N.75-3	WA8N.75-4	WA8N.75-5	629
	1800	143T	WA4N001-3	WA4N001-4	WA4N001-5	400
1	1200	145T	WA6N001-3	WA6N001-4	WA6N001-5	486
	900	182T	WA8N001-3	WA8N001-4	WA8N001-5	830
	3600	143T	WA2N1.5-3	WA2N1.5-4	WA2N1.5-5	438
1.5	1800	145T	WA4N1.5-3	WA4N1.5-4	WA4N1.5-5	445
	1200	182T	WA6N1.5-3	WA6N1.5-4	WA6N1.5-5	573
	900	184T	WA8N1.5-3	WA8N1.5-4	WA8N1.5-5	900
2	3600	145T	WA2N002-3	WA2N002-4	WA2N002-5	458
	1800	145T	WA4N002-3	WA4N002-4	WA4N002-5	463
	1200	184T	WA6N002-3	WA6N002-4	WA6N002-5	630
	900	213T	WA8N002-3	WA8N002-4	WA8N002-5	1138
3	3600	145T	WA2N003-3S	WA2N003-4S	WA2N003-5S	583
	3600	182T	WA2N003-3	WA2N003-4	WA2N003-5	583
	1800	182T	WA4N003-3	WA4N003-4	WA4N003-5	592
	1200	213T	WA6N003-3	WA6N003-4	WA6N003-5	823
	900	215T	WA8N003-3	WA8N003-4	WA8N003-5	1364
5	3600	184T	WA2N005-3	WA2N005-4	WA2N005-5	742
	1800	184T	WA4N005-3	WA4N005-4	WA4N005-5	682
	1200	215T	WA6N005-3	WA6N005-4	WA6N005-5	1088
7.5	3600	184T	WA2N7.5-3S	WA2N7.5-4S	WA2N7.5-5S	1012
	3600	213T	WA2N7.5-3	WA2N7.5-4	WA2N7.5-5	1012
	1800	213T	WA4N7.5-3	WA4N7.5-4	WA4N7.5-5	920
10	3600	215T	WA2N010-3	WA2N010-4	WA2N010-5	1104
	1800	215T	WA4N010-3	WA4N010-4	WA4N010-5	1058
15	3600	215T	WA2N015-3S	WA2N015-4S	WA2N015-5S	1535



Discount Category **16**