



### NEMA Frame

Performance - Page 53  
Dimensions - Page 35

### Foot Mounted

3PH, 60 Hz

Cast Iron Construction

1- 200HP



EPACT  
C.C. 047A

#### Features:

- Motor meets EPACT Efficiency requirements  
(Part No's CC2/4/6)
- Totally Enclosed Fan Cooled Enclosure
- Severe Duty
- IP55 degree of protection
- NEMA Design B
- Class F insulation
- Service Factor 1.15 (1.0 -208V)
- C Faces available
- Liquid painted with Synthetic Enamel paint on Alkyd based high build primer (ASTM Salt Spray life > 200 hrs)
- Easy conversion to F1, F2
- Double drilled feet (Where indicated)
- Double Shielded Ball Bearings up to 215T frame, regreasable bearings frame 254T and above.
- Drainage holes in lowest points of the motor
- **CSA approved for Class I ; Division II ; Groups A,B,C & D**
- Warranty: 2 years

HP	RPM	FRAME	208-230/460V	575V	LIST
1	1800	143T	CC4N001-2	CC4N001-5	284
	1200	143/5T	CC6N001-2	CC6N001-5	367
	900	182T	CC8N001-2	CC8N001-5	490
1.5	3600	143T	CC2N1.5-2	CC2N1.5-5	330
	1800	143/5T	CC4N1.5-2	CC4N1.5-5	330
	1200	182T	CC6N1.5-2	CC6N1.5-5	483
2	900	182/4T	CC8N1.5-2	CC8N1.5-5	618
	3600	143/5T	CC2N002-2	CC2N002-5	350
	1800	143/5T	CC4N002-2	CC4N002-5	353
3	1200	182/4T	CC6N002-2	CC6N002-5	537
	900	213T	CC8N002-2	CC8N002-5	832
	3600	182T	CC2N003-2	CC2N003-5	467
5	1800	182T	CC4N003-2	CC4N003-5	470
	1200	213T	CC6N003-2	CC6N003-5	695
	900	213/5T	CC8N003-2	CC8N003-5	927
7.5	3600	182/4T	CC2N005-2	CC2N005-5	557
	1800	182/4T	CC4N005-2	CC4N005-5	513
	1200	213/5T	CC6N005-2	CC6N005-5	870
10	900	254T	CC8N005-2	CC8N005-5	1332
	3600	213T	CC2N7.5-2	CC2N7.5-5	813
	1800	213T	CC4N7.5-2	CC4N7.5-5	736
15	1200	254T	CC6N7.5-2	CC6N7.5-5	1119
	900	254/6T	CC8N7.5-2	CC8N7.5-5	1569
	3600	213/5T	CC2N010-2	CC2N010-5	879
20	1800	213/5T	CC4N010-2	CC4N010-5	811
	1200	254/6T	CC6N010-2	CC6N010-5	1529
	900	284T	CC8N010-2	CC8N010-5	1855
25	3600	254T	CC2N015-2	CC2N015-5	1383
	1800	254T	CC4N015-2	CC4N015-5	1216
	1200	284T	CC6N015-2	CC6N015-5	1912
30	900	284/6T	CC8N015-2	CC8N015-5	2307
	3600	254/6T	CC2N020-2	CC2N020-5	1529
	1800	254/6T	CC4N020-2	CC4N020-5	1395
40	1200	284/6T	CC6N020-2	CC6N020-5	2339
	900	324T	CC8N020-2	CC8N020-5	3139
	3600	284TS	CC2N025-2	CC2N025-5	1985
50	1800	284T	CC4N025-2	CC4N025-5	1781
	1200	324T	CC6N025-2	CC6N025-5	2887
	900	324/6T	CC8N025-2	CC8N025-5	3472



Discount Category **52**